

J1-89B

Compliant to **CE**

FEATURES AND CHARACTERISTICS

- Designed to safeguard security-sensitive areas
- Just a press of switch and immediate scanning begins
- An audio tone and bright LED alert for operators
- 9-volt battery power required
- Low battery warning signal
- Headphone jack for private screening
- High impact ABS injection molded plastic structure
- CE Complied
- No False Alarms
- Instant Response to All metals
- 1 Year Warranty on All Models

SPECIFICATION

J1-89B					
Dimensions:	Weight (Kg)	Width (mm)	Thickness (mm)	Length (mm)	
	295	65	24	390	
Target Sensitivity	Medium Pistol	Razor Blade	Coin	Paper Clip	Hat Pin
	120mm	40mm	30mm	5mm	25mm
Controls	On / Off Switch				
Operating Temperature	-20°C to +65°C				
Storage Temperature	-25°C to +75°C				
Humidity	98%				
Battery	One 9 Volt block battery MN1604, 6LR61 or Equivalent alkaline disposable or rechargeable				
Operating Time	95 hours continuous at +25°C (alkaline battery)		55 hours continuous at +25°C (rechargeable battery)		
Full Battery Management System	Precision monitoring. Low voltage is signaled in two stages: Yellow LED lights warning the user that the battery will need replacing or recharging in near future. When the battery is exhausted a continuous audio and Yellow visual alarm signal is produced.				
Alarm Indication	Piezo audio alarm and High intensity LED and Earphone Jack Socket				