




6 inch Speed Dome

CC620



1/6" Sony Super HAD Exview CCD Color Day & Night Speed Dome ideal for meeting needs of following moving people / objects and surveillance of pre-defined locations.

FEATURES AND CHARACTERISTICS



Uses High resolution 1/6 Sony Super HAD Exview CCD sensor with resolution of 480TVL (Color) / 520TVL (B/W) complete with Auto Iris and Auto Focus Lens for precise video image processing when viewing.



Optical Zoom of 25X and Digital Zoom of 12X (Total 300X Zoom)



High sensitivity of 0.1Lux in Color Mode and 0.01Lux in B/W Mode and high S/N Ratio for better video images in different environments



137 preset points in 360° Continuous Rotation function provides monitoring of targets more accurately and quickly just like the eye.

SPECIFICATION

	CC620
Image Sensor	1/6" Exview HAD CCD
Effective Pixels	752(H) x 1064(V) – PAL
Lens	25X, f=2.4 to 60mm (F1.6 to F2.7)
Digital Zoom	12X (300X with optional zoom)
Angle of View (H)	48°; 27°
Object Distance	35mm (wide end), 800mm (tele end)
Sync. System	Internal / External (V-Lock)
Min. Illumination	Color Mode: 0.1Lux / B/W Mode: 0.01Lux
S/N Ratio	More than 50dB
Electronic Shutter	Auto: 1/1 ~ 1/0,000sec./Manual
White Balance	Auto, ATW, indoor, outdoor, one push WB, manual WB
Gain	Auto / Manual (-3 to 28dB), 16 x 2dB step
AE Control	Auto, Manual, priority mode, bright, EV compensation, back light compensation
EV Compensation	-10.85 to 10.5dB
BLC	Auto / Manual
Cam. Operation Switch	Auto (Sensitive: H, L), On-Push AF, Zoom Trigger AF
Pan	360° continuous
Tilt	0° ~ 90°
Pan/Tilt Accuracy	±0.3°
Manual Pan/Tilt Speed	0.3° ~ 120°/sec
Preset Position	137 positions
Instant Flip	180°
Preset Recall Speed	150°/sec
Address Setting	1 ~ 64
Control Interface	RS-485
Cable Requirement	UL24AWG x 2C Twisted Pair (recommend)
Power	DC 6~12V / 2.7W (typical)
Weight (N.W / G.W)	2.9kg / 3.6kg (Indoor), 3.3kg / 4kg (Outdoor)
Dimension (W) x (H)mm	229 x 245 (Indoor), 214 x 238 (Outdoor)
Operating Temperature	-20°C ~ +50°C
Operating Humidity	0% ~ 90%
Certification	FCC, CE, IP66