

FS-DV1010U



FEATURES AND CHARACTERISTICS



Full video and audio interface solution via USB.
It converts analog signal to digital output for your computer.



You can browse 16 programs on a monitor simultaneously.
OSD function, display the channel no. and volume in the monitor.
It can catch static and dynamic pictures.



Video output: serial data USB2.0 standard compliant.
FULL DL high resolution: PAL352*288, 640*576, 720*576.



It can compress the TV programs to the format files of MPEG-1, MPEG-2, MPEG-4.
With functions of recording TV programs.



Supports WINDOWS2000/XP with children-locked function.



Time shift (TS) function, it can help to pause programs. The video adapter will record programs stealthily allowing you to concentrate on other things. When you come back, a click on the mouse will allow you to resume watching the program.

SPECIFICATION

SPECIFICATION		FS-DV1010U	
Supporting Formats	MPEG1.MPEG2.MPEG4 compressed format	625/50 (PAL) up to 720×576@25fps	
		625/60 (NTSC) up to 720×480@30fps	
	HDTV MPEG collection		
	CBR/VBR compressed format (up to 15MBIT/SEC)		
Video In	With function to adjust GOP frame (I,B,P frame)		
	With function to AUTO adjust frame/scene format		
	With function converter from 4:2:2 to 4:2:0		
	With technology of digital sound down		
	Supports 3:2 PULLDOWN (film format)		
	With function to test the scene changing		
	Support Program& Transport stream output		
	With AUTO separation for VBI Data		
	With function timing to record		
	Audio	H / V frequency movement test	B frame +296 (H)× + 184 (V)
P frame +326 (H)× + 184 (V)			
Half image precision			
Audio	Supports MPEG-1 layer II		
	Supports 32KHz, 44.1KHz,48KHz sampling rate		
	Supports 448kbit/sec Data format USB outlet		
	Supports USB2.0 (with USB1.1 too)		