

# TPT-BNC & TPR-BNC



Miniature BNC Connector Formation.

Up to 1800m transmission distance.

Low Power Consumption.

Easy Installation.

## SPECIFICATION

	TPT-BNC
Operating Voltage	DC 12V
Consumption	0.3W
Amplification	5km / 5MHz
Max. Transmission	1800m
Twisted Pair Output	2 x 2Vpp
Frequency Response	+0 / 0.5dB (5MHz)
Source Impedance	120ohm
Video Input Signal	1Vpp / 75ohm
Termination Video	75ohm
Ambient Temperature	-10°C to +60°C
Weight	Approximately 30g
Dimension (L x D)	47mm x 18mm

## SPECIFICATION

	TPR-BNC
Operating Voltage	DC 12V
Consumption	0.3W
Equalizing / Adjustment	0 – 30dB at 50Hz – 10MHz / potentiometer
Max. Transmission	1800m
Twisted Pair Output	2 x 2Vpp
Frequency Response	+0 / 0.5dB (5MHz)
Source Impedance	100 - 200ohm
Video Input Signal	1Vpp / 75ohm
Termination Video	75ohm
Ambient Temperature	-10°C to +60°C
Weight	40g
Dimension (L x D)	47mm x 18mm

## CONNECTION DIAGRAM

